

**Certifications**

Approved by ERDF

**Section**

MV Sets

**Application**Field  
Laboratory**PRODUCT BENEFITS**New generation of Tools  
Spare blades included**TOOL CAPACITY**

<b>Diameter</b>	16 - 58 mm 0,630 - 2,283 inch
<b>Section according to voltage rating</b>	50 - 630mm <sup>2</sup>
<b>Chamfer on peelable semi-conductor</b>	Yes
<b>Chamfer on bonded semi-conductor</b>	Yes

**TOOL DIMENSIONS**

<b>Length</b>	575 mm
<b>Width</b>	470 mm
<b>Height</b>	145 mm
<b>Weight without box</b>	10 Kg
<b>Packaging</b>	Case

**ALROC SAS**Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Full kit for distribution underground cable 50 mm<sup>2</sup> up to 630 mm<sup>2</sup>

**TO DO WHAT**

Tools included in the kit CNPT/630-2016 enable the user to splice each layer of distribution underground cable ranging from 50 mm<sup>2</sup> up to 630 mm<sup>2</sup> in 12/20 kV, prior to junctions or terminations installation.

For any other voltage rating, please check the outer diameter capacity of each tools included in the kit

**Associated tool**

CKM-HTA-630-NG - Case for self service kit for MV 630 NG case

AGPB3 - Pliers for lead sheath 26 - 52 mm / 1,024 - 2,047 in

**Case**

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

MF2/60 - Multifonction tool for outer sheath and insulation

MF1+/60 - Tool for bonded semiconductor and peelable with stylus

SRC-D - Scoring stylus for peelable semiconductor with chamfer on the transition

ALROC-FENTE - Tool to perform slits on cable's outer sheath

EV/NPT - Tool to spread PE outer sheath with aluminium screen

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

LIGAREX - Clamping tool with return spring for straps

GRI - Scraper for residues of bonded semiconductor

SCH - Chamfering stylus for insulation

LMF2 - Qty 2 - 2 spare blades for outer sheath and primary insulation

LASCR1 - Qty 2 - 2 spare blades for bonded semiconductor

LS-CD - Qty 2 - 2 Spare blades for semiconductor scoring with chamfer

LSCH - Qty 2 - 2 spare blades to chamfer insulation

LFE-V - Qty 2 - 2 spare blades split outer sheath + Screw

MV cables Tools

# CNPT/630-2016



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Section according to voltage rating	Chamfer on peelable semi-conductor	Chamfer on bonded semi-conductor	Length	Width	Height	
CNPT/630-2016	16 - 58 mm 0,630 - 2,283 in	50 - 630mm <sup>2</sup>	Yes	Yes	575 mm 22,638 in	470 mm 18,504 in	145 mm 5,709 in	case