

**Certifications**

Approved by ERDF

**Section**

MV Outer sheath

**Application**Field  
Laboratory**PRODUCT BENEFITS**

Made in bronze aluminium for added durability

**TOOL CAPACITY****Diameter** 20 - 30 mm  
0,787 - 1,181 inch**C33-226 Vinyl /  
UTE C33-223** 50 to 240 mm<sup>2</sup>**NFC33-223 /  
HN33S23** 50 to 95 mm<sup>2</sup>**TOOL DIMENSIONS****Length** 180 mm**Width** 28 mm**Height** 26 mm**Weight without box** 0,17 Kg**Packaging** None**ALROC SAS**Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

## Tool to spread PVC outer sheath with aluminium screen

**TO DO WHAT**

The EV2000 150-240 enables the user to spread the tabs of the PVC outer sheath with glued aluminium screen (among them : cable C33-226 Vinyl, UTE C33-223, NFC33-223, HN33S23) in order to ease the positioning of the screen ring under the outer sheath

**Associated tool**

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

MV cables Tools

# EV2000 150-240



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		C33-226 Vinyl / UTE C33-223	NFC33-223 / HN33S23	Length	Width	Height	
EV 150/240	25 - 40 mm 0,984 - 1,575 in	-	150 to 240 mm <sup>2</sup>	180 mm 7,087 in	32 mm 1,260 in	26 mm 1,024 in	none
EV 630	40 - 60 mm 1,575 - 2,362 in	630 mm <sup>2</sup>	630 mm <sup>2</sup>	180 mm 7,087 in	36 mm 1,417 in	28 mm 1,102 in	none
EV2000 150-240	20 - 30 mm 0,787 - 1,181 in	50 to 240 mm <sup>2</sup>	50 to 95 mm <sup>2</sup>	180 mm 7,087 in	28 mm 1,102 in	26 mm 1,024 in	none