

MV cables Tools

EV/NPT



Certifications

Approved by ERDF

Section

MV Shield

Application

Field

Laboratory



PRODUCT BENEFITS

Limited opening angle given by the tool so that the aluminium will not break

TOOL CAPACITY

Diameter	15 - 240 mm 0,591 - 9,449 inch
----------	-----------------------------------

TOOL DIMENSIONS

Length	230 mm
Width	15 mm
Height	40 mm
Weight without box	0,24 Kg
Packaging	None

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE
Phone: +33 2 43 71 11 80
Fax number : +33 2 43 71 16 51
www.alroc.fr

Tool to spread PE outer sheath with aluminium screen

TO DO WHAT

The EV/NPT enables the user to spread the tabs of the PE outer sheath with glued aluminium screen (among them, cable : C33-226 Popy and Nikol), without damaging the aluminium screen and in order to slide in the screen ring



Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

MV cables Tools

EV/NPT



Part Number	Diameter	Tool capacity	Dimensions			Packaging
			Length	Width	Height	
EV/NPT	15 - 240 mm 0,591 - 9,449 in		230 mm 9,055 in	15 mm 0,591 in	40 mm 1,575 in	none