

# MV cables Tools

## GFE-TMG



### Certifications

Approved by ERDF

### Section

MV Accessories

### Application

Field  
Laboratory



### PRODUCT BENEFITS

Ensure a good penetration of the pikes of the screen connector into the aluminium screen of the cable  
Quick set up on the ROTO-TMG

### TOOL CAPACITY

|          |                                  |
|----------|----------------------------------|
| Diameter | 16 - 60 mm<br>0,630 - 2,362 inch |
|----------|----------------------------------|

### TOOL DIMENSIONS

|                    |        |
|--------------------|--------|
| Length             | 75 mm  |
| Width              | 45 mm  |
| Height             | 50 mm  |
| Weight without box | 0,2 Kg |
| Packaging          | None   |

### ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE  
Phone: +33 2 43 71 11 80  
Fax number : +33 2 43 71 16 51  
www.alroc.fr

## Roller block for ROTO-TMG to tighten the outer sheath over screen connection

### TO DO WHAT

The GFE-TMG for ROTO-TMG, enables the user to tighten the outer sheath on the pikes of the screen connector

It also enables the user to distort the sectors of the core cable



### Associated tool

ROTO-TMG - Connector holder for bolted and clamping connections

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

LIGAREX - Clamping tool with return spring for straps

MV cables Tools

# GFE-TMG



| Part Number | Diameter                       | Tool capacity | Dimensions        |                   |                   | Packaging |
|-------------|--------------------------------|---------------|-------------------|-------------------|-------------------|-----------|
|             |                                |               | Length            | Width             | Height            |           |
| GFE-TMG     | 16 - 60 mm<br>0,630 - 2,362 in |               | 75 mm<br>2,953 in | 45 mm<br>1,772 in | 50 mm<br>1,969 in | none      |