

Certifications

Approved by ERDF

Section

MV Accessories

Application

Field

Laboratory

**PRODUCT BENEFITS**

Circular abrasion to ensure a good sealing of the accessory
 Deep abrasion on 50mm (1,969 in) in one turn

TOOL CAPACITY

Diameter 16 - 60 mm
 0,630 - 2,362 inch

Abrasion length 50 mm / 1,969 in

TOOL DIMENSIONS

Length 85 mm

Width 40 mm

Height 45 mm

Weight without box 0,23 Kg

Packaging None

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
 FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Cartidge for ROTO-TMG dedicated to sheath abrading

TO DO WHAT

The K7/GRATT for ROTO-TMG enables the user to abrade the outer sheath of the cable in order to ensure a good sealing of the cable joint on termination on the cable

**Spare part**

LRTT - Spare blade sheath abrading (order by 2)

Associated tool

ROTO-TMG - Connector holder for bolted and clamping connections

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

C-RTT - Tool to replace blade for abrasion

MV cables Tools

K7/GRATT



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Abrasion lenght	Length	Width	Height	
K7/GRATT	16 - 60 mm 0,630 - 2,362 in	50 mm / 1,969 in	85 mm 3,346 in	40 mm 1,575 in	45 mm 1,772 in	none