

MV cables Tools

KIT-AMSUD



Section

MV Sets

Application

Field

Laboratory



PRODUCT BENEFITS

Work on a very extensive selection of cable
Very precise

TOOL CAPACITY

Diameter 16 - 58 mm
0,630 - 2,283 inch

Section according to voltage rating 50 - 630mm²

TOOL DIMENSIONS

Length 390 mm

Width 310 mm

Height 145 mm

Weight without box 7,5 Kg

Packaging Case

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE

FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Full kit for stripping (splicing) Primary distribution underground power cables

TO DO WHAT

The KIT-AMSUD enable the user to splice any medium voltage primary distribution underground power cables with peelable (easypeel) or bonded semi-con. It also includes the tool to perform the grounding of cable with aluminium shield.



Associated tool

K7/GRATT - Cartidge dedicated to sheath abrading, to be mounted on tool ROTO-TMG

ALROCRAN - Tightening pliers

Case

MF3/60-C - Multifunction tool for sheath, peelable semiconductor with chamfer, insulation

SCH - Chamfering stylus for insulation

CWB/18-60-FEP - Tool to remove bonded semiconductor with chamfer on the semiconductor cutback

ROTO-TMG - Connector holder for bolted and clamping connections

GFE-TMG - Roller block for ROTO-TMG to tighten the outer sheath over screen connection

ALROC-FENTE - Tool to perform slits on cable's outer sheath

EV/NPT - Tool to spread PE outer sheath with aluminium screen

LIGAREX - Clamping tool with return spring for straps

MV cables Tools

KIT-AMSUD



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Section according to voltage rating	Length	Width	Height	
KIT-AMSUD	16 - 58 mm 0,630 - 2,283 in	50 - 630mm ²	390 mm 15,354 in	310 mm 12,205 in	145 mm 5,709 in	case