

Section

MV Outer sheath

Application

Field

**PRODUCT BENEFITS**

The frame on which the blade is mounted acts like a thrust preventing any cut over 4 mm / 1.57inch

TOOL CAPACITY

Diameter 0 - 200 mm
0,000 - 7,874 inch

Cutting thickness 4 mm / .16 inch

TOOL DIMENSIONS

Length 340 mm

Width 50 mm

Height 50 mm

Weight without box 0,24 Kg

Packaging None

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Aluminium strip saw

TO DO WHAT

The SBA saw enables the user to cut the armouring strips or wires of the non energized cable

**Spare part**

LSBA - Spare blade for aluminium armouring

Associated tool

SBI - Live working aluminium strip saw (1000 V)

PF3/06 - Pliers to remove LC Shield (Longitudinally Corrugated shield)

MV cables Tools

SBA



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Cutting thickness	Length	Width	Height	
SBA	0 - 200 mm 0,000 - 7,874 in	4 mm / .16 inch	340 mm 13,386 in	50 mm 1,969 in	50 mm 1,969 in	none