

Certifications

EN 60900:2012

Section

LV Live working

Application

Field



PRODUCT BENEFITS

The frame on which the blade is mounted, acts like a thrust preventing any cut over 4mm / 0,157 in

TOOL CAPACITY

Diameter 10 - 200 mm
0,394 - 7,874 inch

Cutting thickness max 4 mm / 0,157 in

TOOL DIMENSIONS

Length 350 mm

Width 55 mm

Height 55 mm

Weight without box 0,33 Kg

Packaging None

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE

FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Insulated strip saw / Live working strip saw (1000V)

TO DO WHAT

The SBI enables the user to cut the strip of armored cable when working on energized cables



Associated tool

SBA - Aluminium strip saw

PF3/06 - Pliers to remove LC Shield (Longitudinal Corrugated shield)

LV cables Tools

SBI



| Part Number | Diameter | Tool capacity | Dimensions | | | Packaging |
|-------------|---------------------------------|-----------------------|---------------------|-------------------|-------------------|-----------|
| | | Cutting thickness max | Length | Width | Height | |
| SBI | 10 - 200 mm 0,394 - 7,874 in | 4 mm / 0,157 in | 350 mm 13,780 in | 55 mm 2,165 in | 55 mm 2,165 in | none |